

## **Declaration of Performance** No. 56V-DoP2018-01-10

| 1. Unique identification code of the product-type:     |  | SIGA 56V  |                      |
|--|--|---|----------------------|
| 2. Type, batch or serial number or any other element   |  | 500x250   |                      |
| allowing identification of the construction product as |  | 300%230   |                      |
| required under Article 11(4):                          |  |   |                      |
| 3. Intended use or uses of the construction product,   |  | Slate and carbonate slate for discontinuous roofing and |                      |
| in accordance with the applicable harmonized           |  | cladding  |                      |
| Technical Specification, as foreseen by the            |  |   |                      |
| manufacturer:  |  |   |                      |
| 4. Name, registered trade name or registered trade     |  | SIG Roofing   |                      |
| mark and contact address of the manufacturer as        |  | Harding Way, St. Ives, Cambridgeshire, PE27 3YJ         |                      |
| required under Article 11(5):                          |  |   |                      |
| 5. Where applicable, name and contact address of the   |  | N/A   |                      |
| authorized representative whose mandate covers the     |  |   |                      |
| tasks specified in Article 12(2):                      |  |   |                      |
| 6. System or systems of assessment and verification    |  | AVCP System 4   |                      |
| of constancy of performance of the construction        |  |   |                      |
| product as set out in CPR, Annex V:                    |  |   |                      |
| 7. Declared Performance                                |  |   |                      |
| P (1)  | Desfermen  |   | Harmonised technical |
| Essential characteristics Dimensional variation        | Performance  |   | specification        |
|  | 4.5  |   | EN 12226 1-2014      |
| -Nominal thickness                                     | 4.5mm  |   | EN 12326-1:2014      |
| -Individual thickness                                  | 4.5mm (<+/-35%)  |   | -                    |
| -Deviation of length and width                         | Complies<br>Complies                                     |   | -                    |
| -Deviation from edge straightness                      | Complies   |   | -                    |
| -Deviation from rectangularity                         |  |   |                      |
| Mechanical resistance                                  | Transverse:  | 58 N/mm2  | -                    |
| (Characteristic modulus of rupture)                    | Longitudinal: 61 N/mm2<br>0,25% Code: W1(≤ 0,6%)         |   | 1                    |
| Water absorption                                       | $0.25\%$ Code: $W1(\le 0.6\%)$<br>$0.2\%$ ( $\le 20\%$ ) |   | -                    |
| Apparent calcium carbonate  Durability:                | 0,4% (≤ 40%)   |   | 1                    |
| -Water absorption                                      | 0,25% Code: W1(≤ 0,6%)                                   |   | 1                    |
|  | 0,25% Code: W1(≤ 0,6%)<br>Not Required                   |   | 1                    |
| -Freeze-thaw cycling                                   | T1   |   | 1                    |
| -Thermal cycling -Sulfur dioxide exposure              | S1   |   | 1                    |
| -Non-carbonate carbon content                          | 0.50% Complies (≤ 2%)                                    |   | 1                    |
| Release of dangerous substances                        | None in conditions of use as                             |   |                      |
| Release of daligerous substances                       | roofing or external cladding                             |   |                      |
| External fire performance                              | Deemed to satisfy  |   |                      |
| Reaction to fire                                       | Deemed to satisfy  Deemed to satisfy class A1            |   |                      |
| Reaction to Inc Decinica to Satisfy class A1           |  |   |                      |

- 8. The performance of the product identified in Points 1 and 2 is in conformity with the declared performance in point.
- 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

T. WHY

Name and function: Tony Wright, Procurement Director

Place of issue: SIG Roofing, Harding Way, St. Ives, Cambridgeshire, PE27 3YJ Date of issue: 10/01/2018



