

1	Unique identification of the product type	Fibre cement slates and accessories Smooth Square Edge	
2	Identification	Each slate is provided with a production stamp	
3	Intended use	Roofing and cladding	
4	Name and contact address of manufacturer	SIGA Man-Made Slate Harding Way, St Ives, Cambridgeshire, PE27 3YJ Tel: 01480 466777 Email: info@sigaslate.co.uk Web: www.sigaslate.co.uk	
6	System of assessment and verification of consistency of performance	3	
7	The declaration of performance concerns a construction product covered by a harmonised standard	The manufacturer executes the type test and the factory production control. The notified body WFRGENT (NB1173) has executed the fire tests.	
9	Declared performance:		
	Essential characteristics	Performances	Harmonised standard
	Dimensions	Minimum: 200 x 200 x 4mm Maximum: 600 x 600 x 4mm	EN 492:2012 + A1:2016
	Fire reaction	A2-s1, d0	
	External fire performance	Broof	
	Mechanical resistance	h ≤ 35cm ≥ 30 Nm/m 35 < h ≤ 45cm ≥ 40 Nm/m 45 < h ≤ 60cm ≥ 45 Nm/m	
	Dimensional variations	Length: ± 3mm Width: ± 3mm Thickness: +25% to -10% of nominal value	
	Water permeability	No water drops	
	Durability against warm water	RL ≥ 0.75	
	Durability against soak - dry	RL ≥ 0.75	
	Durability against freeze - thaw	RL ≥ 0.75	
	Durability against heat - rain	Pass	
	Dangerous substances	None	
10	Performance of the product described in points 1 and 2 are in accordance with the declared performances in point 9. This declaration is issued under the sole responsibility of the manufacturer referred to in point 4.		

Signed on behalf of the manufacturer by:



Andrew Wakelin
Managing Director
SIG UK Exteriors
14 June 2017