

SIGA Quebec

DoP Reference: SIGA Quebec UK CA DOP V1 November 2022

1. **UNIQUE IDENTIFICATION CODE OF PRODUCT TYPE:** SIGA Quebec
2. **TYPE, BATCH OR SERIAL NUMBER OR OTHER ELEMENT ALLOWING IDENTIFICATION OF THE CONSTRUCTION PRODUCT – ARTICLE 11(4)**
See product label and associated documents
3. **INTENDED USE OR USES OF THE CONSTRUCTION PRODUCT, IN ACCORDANCE WITH THE APPLICABLE DESIGNATED TECHNICAL SPECIFICATION**
Slate and carbonate slate for discontinuous roofing and cladding
4. **NAME, REGISTERED TRADE NAME OR TRADE MARK AND CONTACT ADDRESS OF THE MANUFACTURER – ARTICLE 11(5)**
SIGA, SIG Roofing, Harding Way, St Ives, Cambridgeshire, PE27 3YJ
5. **NAME AND ADDRESS OF THE AUTHORISED REPRESENTATIVE WHOSE MANDATE COVERS THE TASKS SPECIFIED IN ARTICLE 12(2)**
N/A
6. **SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF THE CONSTRUCTION PRODUCTS AS SET OUT IN ANNEX V**
4
7. **NAME AND IDENTIFICATION NUMBER OF THE NOTIFIED BODY CONCERNING A CONSTRUCTION PRODUCT COVERED BY A DESIGNATED STANDARD**
N/A
8. **NAME AND IDENTIFICATION NUMBER OF THE UK TECHNICAL ASSESSMENT BODY CONCERNING A CONSTRUCTION PRODUCT COVERED BY A TECHNICAL ASSESSMENT DOCUMENT**
N/A
9. **DECLARED PERFORMANCE ACCORDING TO:** EN 12326-1:2014

Essential Characteristics	Performance				Designated Standard
Dimensional Variation					
Deviation from declared length:	+/- 5mm				EN 12326-1:2014
Deviation from declared width:	+/- 5mm				
Deviation from rectangularity/squareness:	+/- 1%				
Deviation from straightness of edges:	<5mm or +/- 1%				
Slate Type:	Very Flat	Flat	Normal	Non Flat	
Deviation from flatness:	<0.9%				
Nominal thickness and variation:	4-9mm +/-35%				
Mechanical Resistance:	Characteristic MOR:				
	Transverse: 52N/mm ²		Longitudinal: 60N/mm ²		
Durability					
Water absorption:	W1 (<0.6%) 0.3%				
Freeze thaw:	Not Required				
Thermal cycle test:	T1				
Sulphur dioxide exposure tests:	S1				
Carbonate content:	(<=20%) 0.2%				
Non-carbonate carbon content:	(<2.0%) 0.6%				
External Fire Performance:	Deemed to satisfy				EC Decision 2000/553/EC
Reaction to Fire:	Deemed to satisfy Class A1				EC Decision 96/603/EC as amended
Dangerous substance emission	None in conditions of use as roofing or external cladding				

The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of SIGA, SIG Trading Ltd:



Steve Marr - SIG UK Compliance Director
SIG Trading Ltd, Sheffield - 30/11/22